

# **Temperature Data Logger EBI 12**

for food control during pasteurization

## **BLUE LINE**

The EBI 12 data logger is designed for temperature Measurement in bottles and beverage cans is suitable.

- · High-quality stainless-steel housing
- · Axial design
- M10 thread for attachment to the probe
- Application range from -55 °C to +150 °C
- High temperature accuracy of up to ±0.1 °C
- Version with two measuring channels
- · Temperature sensor 6 mm, rigid

#### **Technical Data:**

0	FE 90 .450.90
Operating	-55 °C +150 °C
temperature	
Measurement range	-55 °C +150 °C
Accuracy	± 0.5 °C (-55 °C40 °C)
	± 0.2 °C (-40 °C 0 °C)
	± 0.1 °C (0 °C +150 °C)
Resolution	0.01 °C
Data memory	2x 13,920 measurements
Sensor	PT1000, class A
Measurement interval	1 s 24 hours
Real-time data	No
transmission	
Storage temperature	-20 °C +70 °C
Measurement modes	endless measurement
	measurement from the start time
	<ul> <li>Measure software until memory is</li> </ul>
	full
	Start- / Stop measurement
Battery	Lithium, 3.6 V,
,	User-replaceable
Dimensions	(Ø x H) 48 mm x 24 mm
Weight	app. 90 g
Housing material	316 L stainless steel / PEEK
Protection class	IP68
Factory Calibration	-20 °C, 0 °C, +60 °C and +121 °C
Certificate	25 5, 5 5, 155 5 4114 1 121 5
Oortinoato	

### **EBI 12-T461**



#### **Standards and Directives:**

- (EC) 1935/2004
   Materials and articles which come into contact with food
- 2014/53/EU
   Radio Equipment Directive RED

Туре	Description	Part No.
EBI 12-T461	radial, 135 mm needle length	1340-6623

